
## **Technical information**

Productnumber: 40-2025V





## **Product description**

Mobile collection tray with hot-dip galvanized grid. This drip tray rests on two fixed castors and two swivel castors with locks. The drip tray can accommodate two 200-litre drums and has a collection volume of 243 litres. Attention, drum rack not supplied as standard!

Guideline for storage and temporary storage for drip trays with regard to fire safety, occupational safety and environmental safety in accordance with PGS 15 (publication series of hazardous substances):

A storage facility must be constructed in such a way that leaked or spilled hazardous liquid falls into a collection container is collected. To this end, the collection container must have a capacity of at least 110% of the largest package. However, if 10% of the total content of the packages is more than 110% of the content of the largest package, then the collection capacity must be equal to 10% of the total content of the packages together. The collection container must be sufficiently resistant to the stored liquids.

The collection capacity only applies to liquids. Empty, uncleaned packaging does not count. The collection facility may also be realized in storage. The choice of location for the collection facility may depend on the hazardous liquids stored. Kruizinga.nl is not liable for the type of use!

Please note! Any form of modification is not allowed. If this is the case, all regulations will lapse.

## **Specifications**

Article arrangement: New Version: for 2 x 200 l drums

Walls: walls closed

Wheels front: 2 castor wheels, polyamide, 125 mm Wheels back: 2 bearing wheels, polyamide 125 mm

Surface treatment: galvanized Internal length (mm): 1200 Internal width (mm): 800 Internal height (mm): 515 Collection volume (ltr): 243 Type: Retention Basin

Material: steel

Floor: with galvanized grid Subgroup: Mobile trays Colour: colorless Length (mm): 1320 Width (mm): 800 Height (mm): 1115 Weight (kg) 82

Type number: 40-20











## **Technical information**

Productnumber: 40-2025V











