

Image not found or type unknown



Technical information

Productnumber : 75.340.884.750



Product description

Apparatus casters swivel castor made of pressed sheet steel, bolt hole fitting, gray non-stretching thermoplastic rubber tire, precision ball bearing, Wheel-Ø 75mm, 100KG

wheel: gray non-stretching thermoplastic rubber tire, with wheel center made of polypropylene, precision ball bearing, double wheel mounting

Advantages: Versatile wheel for applications on flat surfaces. Dual wheels for high load capacity with low build height.

Applications: Excellent for static applications under load, such as heavier cabinets, freezers, etc.

Suitable surface: Flat surface, without obstacles.

Suitable environment: Dry and not permanently damp. For light acids and bases.

Specifications

Article arrangement: New

Version: Ø 75x48 mm

Top: bolt hole 10 mm

Colour: colorless

Length (mm): 75

Height (mm): 99

Wheel bearing: ball bearing

Wheels diameter: 75

Type: castor wheel

Material: thermo rubber

Bolt hole: Ø 10 mm

Surface treatment: galvanized

Width (mm): 48

Loading capacity (kg): 100

Type number: 340884750

Additional specifications: double wheel

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment