

Image not found or type unknown.



Technical information

Productnumber : 75.346.880.750



Product description

Swivel castor made of pressed steel, plate fitting, gray non-elastic thermoplastic tire, plain bearing, wheel Ø 75 mm, 100KG

Wheel: gray non-elastic thermoplastic rubber tire, with polypropylene wheel core, plain bearing, double wheel fixing

Advantages : Versatile wheel for applications on flat surfaces. Dual wheels for high load capacity at low construction height.

Applications: Excellent for static applications under load, such as heavier cabinets, freezers, etc.

Suitable surface: Flat, unobstructed surface.

Suitable environment: Dry and not permanently damp. For light acids and bases.

Specifications

Article arrangement: New

Version: Ø 75x48 mm

Top: base plate 60x60 mm

Bolt hole: Ø 6.2 mm

Surface treatment: galvanized

Width (mm): 48

Loading capacity (kg): 100

Type number: 346880750

Additional specifications: double wheel

Type: castor wheel

Material: thermo rubber

Hole centres: 42x42 mm

Colour: colorless

Length (mm): 75

Height (mm): 100

Wheel bearing: sliding bearing

Wheels diameter: 75

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment