

Image not found or type unknown.



Technical information

Productnumber : 75.246.612.800



Product description

for more information see manual.

Advantages: The solid rubber tires have a hardness of 80 ° Shore A and offer good driving characteristics, roll silently, are shock and impact resistant, corrosion resistant and have an average rolling resistance.

Applications: Industrial carts, material handling in factories, waste containers, transport containers, metal and chemical companies, roll containers for medium-heavy loads, tool trolleys, warehouse carts. The belt may leave black marks.

Suitable environment: Dry and not permanently damp. With mild acids and bases.

Specifications

Article arrangement: New

Version: Ø 80 mm

Top: base plate 105x85 mm

Bolt hole: Ø 9 mm

Surface treatment: galvanized

Width (mm): 27

Loading capacity (kg): 65

Type number: 754661

Type: right wheel

Material: standard rubber band

Hole centres: 80x60 mm

Colour: colorless

Length (mm): 80

Height (mm): 104

Wheel bearing: roller bearing

EAN Code (Gtin) 8719424014501

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment