

Image not found or type unknown.



Technical information

Productnumber : 8613010009

Product description

High-quality ramps suitable for loading light to medium-heavy vehicles such as construction machines, garden machines or ride-on mowers, which are equipped with pneumatic tires or rubber tracks. The driving surface is reinforced at the bottom, which significantly extends the life of the driving plates. Weight per driving plate is 36 kg. The load capacity shown is per set, with an axle distance of 1500 mm. Suitable for a ramp height of 79 to 100 cm.

This ramp is supplied as standard with connection A and a flat floor 1, see detail photos. It is optionally possible to adjust this to your liking, please contact us for the possibilities or indicate your preference during the ordering process.

Specifications

Article arrangement: New

Version: without edge

Top: driving area of anti slip profile

Width (mm): 405

Loading capacity (kg): 3470

Type number: AVS-130

Height difference max (mm): 30% with max. height

Max Height (mm): 1000

Type: acces ramp

Material: aluminium

Length (mm): 3590

Internal width (mm): 325

Weight (kg) 36

Batch (items): 2

Min Height (mm): 790

EAN Code (Gtin) 8719424120738

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment