

Image not found or type unknown



Technical information

Productnumber : 42.199.22.128



Product description

Flexible steel protective bollard for protection of roller and fire doors, transitions on driveways, ramps, etc. against collision damage. The intelligent bollard, equipped with a steel spring in combination with an elastic buffer made of polyurethane, minimizes damage to the post and the vehicle. The protective post can tilt 25 degrees (approx. 310 mm). The striking yellow posts are made of 4.5 mm thick high-quality steel with a diameter of 159 mm and are provided with black signal stripes. The bottom plate has a height of 270 mm and a diameter of 35 mm and is provided with 4 drilled holes with a diameter of 14 mm. screw 8/100 (article number: 42.109.17.393) of 4 x through anchors for concrete floors 12/120 (article number: 42.109.24.665) of 1x ground pipe to be poured into concrete including screws (article number: 42.199.25.395)

Specifications

Article arrangement: New

Version: rotatable crash protection bollard

Subgroup: Protection guards

Surface treatment: plastic-coated

Height (mm): 700

Type number: 42-BP-199

EAN Code (Gtin) 8719424115574

Type: bumper protection

Material: steel

Colour: black/yellow

Width (mm): 159

Weight (kg) 35.5

Additional specifications: only suitable for indoor use!

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment