

Image not found or type unknown



Technical information

Productnumber : 75.100.542.261



Product description

Pneumatic tyre wheel with block tread, roller bearing, Wheel-Ø 260mm, 150KG

Wheel: pneumatic tyre with block tread, with polyamide wheel core, roller bearing,

Advantages: For medium-heavy transport of e.g. shock-sensitive products or on irregular / unpaved surfaces. Low-noise and vibration damping.

Applications: Versatile use for light transport in e.g. offices, warehouses, shops and institutions. Low-noise, impact-resistant and anti-vibration. Swivel castor for light applications. Less suitable for long-term static use under maximum load.

Suitable surfaces: Almost any surface, both indoors and outdoors. Uneven surfaces such as clinkers, damaged floors and near obstacles such as thresholds. Unpaved surfaces.

Suitable environment : Dry and not permanently damp. With weak chemicals.

Specifications

Article arrangement: New

Version: Ø 260 mm

Bolt hole: Ø 20 mm

Length (mm): 260

Loading capacity (kg): 150

Type number: 100542261

Drive width: 85

Type: air tire

Material: rubber

Colour: red/black

Width (mm): 85

Wheel bearing: roller bearing

Wheels diameter: 260

EAN Code (Gtin) 8719424144574

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment