




Technical information

Productnumber : 77-A171070



Product description

Swivel castor with plate and brake - Load capacity 1200 kg

- Swivel castor with plate and brake.
- Clamp and plate made of mechanically welded steel.
- Excellent wear resistance.
- Molded polyurethane tyre.

- Model: Swivel castor
- Ø (mm): 250 mm
- Hub type: BALL BEARING
- Tread width (mm): 50 mm
- Total height (mm): 305 mm
- Centre-to-centre mounting holes: 105 x 80/75 mm
- Max. load (kg): 1200 kg
- Colour: BLACK/BROWN
- EN Norm: EN 12533
- Min. operating temperature (°C): -20 °C
- Max. operating temperature (°C): +60 °C
- Fixing eye Ø (mm): 11 mm
- Mounting type: With base plate
- Base plate length (mm): 135 mm
- Wheel frame material: Steel
- Base plate width (mm): 110 mm
- Stroke (mm): 61 mm
- Tread type: POLYURETHANE
- Use: INDOOR/OUTDOOR GOODS HANDLING

Specifications

Article arrangement: Used

Type: castor wheel with brake



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment

Image not found or type unknown

Version: Ø 250 mm
Top: base plate 105x85 mm
Length (mm): 250
Height (mm): 305
Weight (kg) 10
Type number: A171070
EAN Code (Gtin) 8719424198058

Scan the QR code for more information



Technical information

Productnumber : 77-A171070

Material: polyurethane rolling surface
Bolt hole: Ø 11 mm
Width (mm): 50
Loading capacity (kg): 1200
Wheel bearing: ball bearing
Temperature resistance: -20 / +60°C



KRUIZINGA.NL[®]
Opslag- en transportmiddelen

KRUIZINGA.DE[®]
Lager- und Transportmittel

KRUIZINGA.FR[®]
Stockage et ressources de transport

KRUIZINGA.COM[®]
Material handling equipment