

Image not found or type unknown



Technical information

Productnumber : 75.146.542.260

Product description

Advantages: For medium-heavy transport of, for example, shock-sensitive products or on an irregular / unpaved surface. Low noise and vibration damping.

Applications: Excellent shock absorption. Low rolling resistance on uneven floors. Very floor-saving due to the pneumatic tires.

Suitable surface: Almost any surface, both indoors and outdoors. Uneven surfaces such as clinker bricks, damaged floors and obstacles such as thresholds. Unpaved surfaces.

Suitable environment: Dry and not permanently damp. With weak chemicals.

Specifications

Article arrangement: New

Version: Ø 252 mm

Top: base plate 175x140 mm

Bolt hole: Ø 11 mm

Surface treatment: electro-galvanized

Width (mm): 85

Loading capacity (kg): 150

Type number: 755422

Type: castor wheel

Material: Pneumatic tyre

Hole centres: 140x105 mm

Colour: colorless

Length (mm): 260

Height (mm): 290

Wheel bearing: sliding bearings

EAN Code (Gtin) 8719424013597

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment